







OMEGA - F

ELECTRIC CONNECTION

El. supply 230V AC 50Hz (cable 3Cx2,5), lenght of free end of el.cable 2m, together with cable earth connecting CY6mm, green/yelow ensure customer before instalation of platform.
El. supply must be attach individual elektr. circuit breaker 16A/C and residual current circuit breaker (RCCB) for residual sinusoidal alternating currents 0,03A,type A-G, sensitive residual pulsating direct currents

PILLAR	HEIGHT
A	790
B	900
C	1120
D	1115

UP RZESZOW

POWER SUPPLY (EL. CONTROL BOX)	1x230V	EL. MOTOR:	1,1kW/3x230V	nmot=	1400 1/min
GEAR BOX TYPE:	SRS50/71B14				
	z1=30, z2=130				
i (1)	40				
n3 (1/min)	8,077				
v (m/s)	0,09				
ROPE: DIAMETER:	9 mm	TRACTION ROPE:	2700 mm	DIAMETER	7.1 mm
SUPPORTING ROPE:	3281 mm				
ROPE FIXING:	A50500-000-04	CURRENT COLLECTOR:		A50540-000-00	

LIFT PLUS PL
Kaczmarczyk Spółka Jawna
Ul. Strazacka 33
42-263 Wrzosowa, POLAND

Platform OMEGA-F

SP 5550