



OMEGA-F ELECTRIC CONNECTION

El. supply 230V AC 50Hz (cable 3Cx2.5), length of free end of el.cable 2m, together with cable earth connecting CY6mm, green/yellow ensure customer before installation of platform.

El. supply must be attach individual elektr. circuit breaker 16A/C and residual current circuit breaker (RCCB) for residual sinusoidal alternating currents 0.03A type A-G, sensitive residual pulsating direct currents

Pillars are supplied by LIFT PLUS PL

PILLAR	LENGTH
A	970
B	1120
C	1285
D	1460

Order: ORDER 22.06.2017 PLAWIA 2

POWER SUPPLY (EL. CONTROL BOX) 1x230V | EL. MOTOR: 1,1kW/3x230V | n_{mot}=1400 1/min
 GEAR BOX TYPE: SRS50/71B14 | z1=30, z2=130
 i: 40
 n3 (1/min): 8,077
 v (m/s): 0,09
 ROPE: DIAMETER 9 mm TRACTION ROPE: 9420 mm DIAMETER: 7,1 mm SUPPORTING ROPE: 9957 mm
 ROPE FIXING: AS0500-000-04 | CURRENT COLLECTOR: AS0540-000-00

LIFT PLUS PL

LIFT PLUS PL Kaczmarczyk
 Spółka z ograniczoną odpowiedzialnością
 ul. Strazacka 33, 42-263 Wrzesowa
 POLAND

SP OMEGA-F | SP 5751