



OMEGA-F ELECTRIC CONNECTION

El. supply 230V AC 50Hz (cable 3Cx2,5), lenght of free end of el.cable 2m, together with cable earth connecting CY6mm, green/yelow ensure customer before Instalation of platform.
El. supply must be attach Individual elektr. circuit breaker 16A/C and residual current circuit breaker (RCCB) for residual sinusoidal alternating currents 0,03A,type A-G, sensitive residual pulsating direct currents

| PILLAR | LENGTH | PILLAR | LENGTH |
|--------|--------|--------|--------|
| A | 1235 | G | 1175 |
| B | 1220 | H | 1340 |
| C | 1205 | I | 1270 |
| D | 1195 | J | 1205 |
| E | 1155 | K | 1130 |
| F | 1090 | | |

Order: ORDER 05.07.2017 Ozorków

| | | | | | |
|---|---------------|--------------------|---------------|-----------|-------|
| POWER SUPPLY (EL. CONTROL BOX) | 1x230V | EL. MOTOR: | 1,1kW/3x230V | nmot=1400 | 1/min |
| GEAR BOX TYPE: | SR550/71B14 | | | | |
| i | 40 | | | | |
| n3 (1/min) | 8,077 | | | | |
| v (m/s) | 0,09 | | | | |
| ROPE: DIAMETER:9 mm TRACTION ROPE: 8860 mm DIAMETER:7.1 mm SUPPORTING ROPE: 9534 mm | | | | | |
| ROPE FIXING: | A50500-000-04 | CURRENT COLLECTOR: | A50540-000-00 | | |

LIFT PLUS PL. Koszarynski
Spółka z o.o.
ul. Straszacka 33, 42-269 Wroclaw
POLAND

SP OMEGA-F SP 5776a

