



DISTANCE RING		PILLAR	
Ø50x10		A	810
LENGTH (mm)	NUMBER (pcs.)	B	1005
50	2	C	1290
		D	1270
		E	1235
		F	1175

Order: PSB

POWER SUPPLY (EL. CONTROL BOX)	1x230V	EL. MOTOR:	1,1kW/3x230V	n _{mot} =1400 1/min
GEAR BOX TYPE:	SRS50/71B14			
	z1=30, z2=130			
i (1)	40			
n3 (1/min)	8,077			
v (m/s)	0,09			
ROPE: DIAMETER:	9 mm	TRACTION ROPE: 4380 mm	DIAMETER: 7.1 mm	SUPPORTING ROPE: 5056 mm
ROPE FIXING:	A50500-000-04	CURRENT COLLECTOR:	A50540-000-00	

ELECTRIC CONNECTION

El. supply 230V, AC 50Hz for drive to 1,1kW:
 cable 3Cx1,5/2,5, length of free end of el.cable 2m,
 together with cable earth connecting CY6,
 green/yelow ensure customer before instalation of
 platform.
 El. supply must be attach individual elektr. circuit
 breaker 13A/C and residual current circuit breaker
 (RCCB) 25/0,03A type A-G for residual sinusoidal
 alternating currents and residual pulsating direct
 currents or type B AC/DC sensitive for frequency
 inverter, accordng to local regulations



LIFT PLUS PL
 Kaczmarczyk Spółka Jawna
 Ul. Strazacka 33
 42-263 Wrzosowa, POLAND

SP Omega - F
 SP 5978